

Advanced Series

Multi-Rip saws SCA 320 T 350



The CML Advanced Series is tailored to meet from low to high volume production requirements. With the Advanced Series, you get the features you need, without paying for extras you don't. The SCA 320 T 350 series features a heavy-duty Multi-Rip saws with higher horsepower ratings for higher volume customers. The SCA 450 T 500, SCA 650 T 700 are heavy-duty machines with even more horsepower that provides a wider cutting area possibilities with an high volume environments. Whatever your requirements, Cml offers a Ripsaw to meet your needs.

CML

Cml has industry-leading ripsaws to help you successfully optimize the use of all material. Designed to meet your unique production requirements, the high performance CML multi-rip saws optimize materials and minimize costs. CML multi-rip saws deliver high quality cuts with limitless application possibilities. Whatever your requirements, CML has a ripsaws to help you make the most of every situation.

Cml Features

- Heavy-duty Dip chain feed belt with hardened steel guides
- 5 top pressure roller with Extended pressure board
- Precision surface treated Arbour shaft
- Easy and practical operation clearly displayed via the control panel
- Complete range of optimization solutions

CML ENGINEERING S.R.L.
Advanced Equipment
Intelligent Integration
Experienced Consulting
Incomparable Services
E-mail info@cml-engineering.it



Advanced Series

Multi-Rip saws SCA 320 T 350

Technical Specifications	CML Multi-Rip Saw SCA 320 T 350
Voltage	400V / 50Hz
Dust Connection (MAIN)	300mm diameter port/30 meters per second/7600Mc3/h
Machine Weight	2800Kg
Machine Dimensions	Length 220cm Width 200cm Height 190cm
Main Drive Motor	Hp 30-40-50-60-75 / Kw 22-30-37-44-55
Feed Belt Motor	1.5Kw
Feed Belt Speed	0 to 36 Meters per minute
Pressure Roll Motor	0.75Kw
Maximum pass thru width	830mm
Feed belt width	350mm
Maximum Balde speed	3500 RPM
Maximum board Thickness	130mm (370mm Blade)
Minimum board Thickness	20mm
Minimum board Length	500mm
Maximum distance between fixed blades	320mm
Table working height from floor	780mm
Sound enclosure padding for quite running reducing noise level 15db	
Automatic oil pump for feed chain with failure detection shutoff	
Specifications are subject to change.	



Main Office : Via Torri Bianche 1 - 20059 VIMERCATE (MI) – ITALY
Production : Via G. Galilei, 34/36 – 20060 GESSATE (MI) - ITALY
Tel 0039-02-95384207
Fax 0039-02-95384223

E-mail : info@cml-engineering.it – Web : www.cml-engineering.it